

# SS Vertical Color



## Technical Data Sheet

### ALL PURPOSE VERTICAL ACRYLIC COLORING FINISH

#### PRODUCT DESCRIPTION

SS Vertical Color is a matte acrylic product, richly pigmented, and designed for use over new and old properly prepared concrete surfaces. It is supplied in a variety of colors.

#### BENEFITS AND FEATURES

- It is a coloring and sealing system in one.
- UV Stable for exterior work on buildings, bridges, grottoes and any type of landscaping concrete works.
- Can be used to antique concrete for a natural appearance.

#### RECOMMENDED APPLICATIONS

May be used on concrete decks, floors and walls. May also be used for sealing heavy pores in concrete blocks. SS Vertical Color may be used on any sound, and clean porous surface.

#### TECHNICAL INFORMATION

Solids .....	55.38 +/- 2.0%
Drying Time (to touch) .....	30 - 40 minutes at 77°F
Re-Coat Time .....	2 - 4 hours at 77°F
Foot Traffic .....	n/a
Wheel Traffic .....	n/a
Application Temp .....	above 40°F below 90°F
Theoretical Coverage .....	100 - 125 sq. ft.

*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times.*

#### SPECIFICATIONS/COMPLIANCES

Not applicable.

#### APPROXIMATE COVERAGE RATES

Coverage rates vary depending upon surface porosity and texture, and application method. We highly recommend making a sample board before proceeding.

#### INSTRUCTION FOR USE

**Surface Preparation:** Surface must be clean and free of oil, wax, grease, dirt and sanding dust. Remove all dust with a dust cloth. Do not apply if substrate temperature is below 40 degrees F.

**Application:** Apply with a paint roller, nylon brush or airless sprayer. All surfaces to be coated must be clean and free of contaminants. If more sheen is desired, SS Eposeal 38 may be used to clear coat the surface.

**Antique:** Allow the first SS Vertical Color application to dry. Apply the second coat of a contrasting color with an airless sprayer and wipe off before drying leaving pigment in the low areas to create a natural appearance.

#### CLEAN UP

Use warm water and soap. Clean tools with soapy water immediately after use. Dispose of containers in accordance with local and federal regulations.

#### PRODUCT REMOVAL

Dried, cured SS Vertical Color can be removed by chemical means such as SS Strip-A-Lot or by mechanical means.

#### SHELF LIFE

SS Vertical Color has a shelf life up to one or two years in its original, sealed, unopened container.

#### PACKAGING

SS Vertical Color is packaged in 32 oz., 1 gallon and 5 gallon containers.

#### PRECAUTIONS AND LIMITATIONS

- Protect from freezing and high heat.
- Flash Point >250 degrees F.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- Use impervious gloves for prolonged or repeated contact. Eye irritation may occur. Wear protective goggles. Wash thoroughly after handling.
- Use in well-ventilated area. Inhalation of vapors may cause headaches, nausea, eye and lung irritation as well as narcosis.
- Keep away from children.
- Dispose of the product in accordance with all applicable state and local laws.
- the Statements made within this technical data sheet, SDS, product labels, etc., are guidelines only. the end user should always perform test and product evaluations prior to application to ensure suitability for particular uses.

#### SPECIAL NOTES

Please consult Safety Data Sheet (SDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 866-906-2006.

#### WARRANTY

SS Specialties and its affiliates warrant our products to be of good quality, free of defects and will conform to our published specification in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, SS Specialties will replace defective materials ninety days after SS Specialties has shipped the product. All our warranty and other duties with respect to the quality of materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will SS Specialties be liable for any consequential damages in excess of the purchase price of the product.



[www.ssspecialtiesconcrete.com](http://www.ssspecialtiesconcrete.com)

Distributed by SS Specialties | 121 NE 40th Street | Oklahoma City, OK 73105 USA | Phone 866-906-2006 | Fax 405-525-3367

SSVerticalColorJune2017  
6/21/17